

Technical Information Ceramic Paste Spray



Metal-free high-temperature paste with excellent lubricating effect. Good corrosion protection. Ideally suited for assembly work on ABS brake systems as well as for long-term lubrication of highly loaded sliding surfaces of all kinds. Temperature resistant from -40°C to $+1,400^{\circ}\text{C}$. The removable brush head allows for easy even application of the paste.

For use on:

ABS braking systems, bayonet, plug and screw, pipe, flange joints and fittings

Quality and properties

- - Metal-free lubrication with extreme temperature resistance
 - Facilitates dismantling, even after long periods of operation
 - Prevents corrosion and squeaks
 - Resistant to chemicals and weathering
 - Resistant to salt water, weak acids and bases
 - Non-conductive

Physical and chemical data

- **Basis:** grease very fine ceramic particles
- **Colour:** white
- **Smell:** characteristic
- **Relative density at 20°C :** 0.706 g/ml
- **VOC value:** 60%
- **Vapour pressure at 20°C :** 3,5 - 4 bar
- **Temperature resistance:** -40°C to $+1,400^{\circ}\text{C}$
- **Storage stability:** 10 years if appropriate storage provided ($=10^{\circ}\text{C}$ - 25°C , relative air humidity of max. 60%)
- **Size:** aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- Shake well before use.
- Remove moisture, dirt and grease from part to be sprayed.
- Spray on the surface without the brush and then spread the paste evenly with the brush head.
- Ensure that grating surfaces are not sprayed!

Tips for spray painting

Protect the object and the surrounding area from spray mist. Temperature should range between $+10^{\circ}\text{C}$ and $+25^{\circ}\text{C}$, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 21, 2016

This release replaces all eventually earlier issued versions.

Print date: 20.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com