

Technical Information Tire Paint



White special racing touch-up pencil for the marking of brand tyres, e.g. to point out the brand of the tyre manufacturer.

Quality and properties

- High-grade quality
- Durable gloss
- Excellent adhesion
- Quick-drying
- Weather-resistant
- Scratch-, bump- and impact-resistant
- Very smooth surface avoids the attraction of dirt

Physical and chemical data

- **Basis of the binder:** acrylate co-polymeres
- **Colour:** white
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):
glossy: 60-65 gloss units
- **Efficiency:**
not measurable, due to partial us
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 50 minutes
Cured: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** touch-up pencils with maximum nominal volume 12 ml

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application

- Carefully clean the tyres.
- The surface has to be clean, dry and fat-free.
- Shake the touch-up pencil vigorously before use.
- Apply just one thin coat of lacquer.

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of January 5, 2010
This release replaces all eventually earlier issued versions.

Print date: 27.01.2021

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com