

Technical Information Rust Effect Spray



With this new effect spray you achieve a special rough texture with a visual appearance like rust. If you undercoat selective areas with orange or black paint, you can achieve very individual effects. Suitable for indoor and outdoor objects.

For the demands of DIY, decoration and handicraft. Suitable for metal, wood, glass, stone, ceramics, carton and many coatable plastics.

Quality and properties

- High-quality special paint
- Special, rough texture
- Very good coverage
- Excellent adherence
- Quick-drying
- Suitable for indoors and outdoors applications
- Excellent colour retention: weather-resistant, light-proof, UV-resistant
- Can be recoated well.

Physical and chemical data

- **Basis of the binder:** special lacquer on nitro-combi basis
- **Colour:** rust-brown
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not applicable due to special structure
- **Efficiency:**
Depending on consistence and color of the ground:
400 ml are sufficient for approx. 1.5 m²
150 ml are sufficient for approx. 0.5 - 0.6 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Non-sticky: after approx. 15 minutes
Dry to touch: after 50 minutes
Can be coated with rust-effect spray at any time; with other top coats after approx. 3 hours.
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans with maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

Preparation of the ground:

- Carefully remove loose parts of old paintings and rust.
- Then sand and remove dust.
- The ground has to be clean, dry and free from fat.
- Apply a primer, if necessary, e.g. DUPLI-COLOR Universal Primer
- Prepare coatable hard plastics with DUPLI-COLOR Plastic Primer
- You can create individual effects by priming selective areas with orange or black paint.

Lacquering:

- Cover areas not to be painted.
- Before use, shake the can for 2-3 minutes.
- Test spray to check colour-matching and compatibility at an invisible spot.
- Spray several thin coats in 2 minute intervals.
- Spray from a distance of approx. 25 cm.
- Best results will be achieved at temperatures around 20°C.
- Do not spray over synthetic paints.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 19, 2013

This release replaces all eventually earlier issued versions.

Print date: 20.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com