

## Technical Information Battery Pole Protection Spray



presto Battery Pole Protection Spray protects electrical contacts and battery terminals from oxidation and corrosion. The blue wax ensures a constant flow of electricity and prevents leakage and voltage losses. It extends the life of a battery and prevents acid damage. Good compatibility with plastics.

**Applications:** battery terminals, battery holders, terminals, earth cables

### Quality and properties

- Long-term prevention from corrosion and oxidation
- Safe ignition and bright lighting
- Prevents acid damage
- Insulating effect
- Prevents leakage and contact resistance
- Extends the life of a battery
- Directed jet spray
- Can be sprayed from any angle due to a special 360 ° valve.
- Observe TRG 300

### Physical and chemical data

- **Basis:** Wax
- **Colour:** blue
- **Smell:** waxy
- **Appearance:** fat
- **Relative density at 20°C:** 0.695 g/ml
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Temperature resistant:** -30°C to +130°C
- **pH-value:** neutral
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 400 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Make sure can is at room temperature.
- Application temperature 5-30°C.
- Parts to be protected must be clean and dry.
- Shake can well before use.
- Spray a thin layer of battery terminal protection on the parts to be treated.

### Order informations

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 12, 2014

This release replaces all eventually earlier issued versions.

Print date: 24.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)