

Technical Information Aircondition Cleaner



presto Aircondition Cleaner cleans and freshens air in vehicle air conditioning and circulation systems.

The cleaner forms foam after being applied on the vaporiser and the heating ducts and releases a pleasant fragrance.

Quality and properties

- Lasting protection for smells
- Subtle scent
- Effective cleaning foam
- TRG 300 compliant

Physical and chemical data

- **Basis:** Tenside solution
- **Colour:** white
- **Smell:** Orange
- **Appearance:** white foam
- **Relative density at 20°C:** 0.967 g/ml
- **Coverage:** one can for cleaning of a air-conditioning system
- **pH-value:** 9.5 - 10.5
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Before use, shake the aerosol.
- Before treatment, switch off the engine and the electrical installations.
- Apply the foam to the evaporator of the air conditioning by means of the enclosed adapter.
- Insert the adapter about 30 centimetres into the air inlet of the air conditioning and completely empty the can.
- The location of the air inlet differs per brand, consult your dealer.
- After applying, do not switch on the engine or the electrical installations for at least half an hour.
- In this half hour the foam will break and leave the system through the condensed water outlet as a fluid.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 4, 2016
This release replaces all eventually earlier issued versions.

Print date: 20.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com