

## Technical Information Aerosol Art Clear Lacquer

---



Aerosol Art Clear Lacquer is a crystal-clear coating varnish for spray paints on acrylic or nitro-combi basis, e.g. Aerosol Art spray paints.

### Quality and properties

---

- High-grade acrylic quality
- Excellent adhesion
- Good flow, smooth surface
- Excellent gloss retention
- Very hard surface, good elasticity
- Quick-drying
- Light-proof, UV-resistant (non-yellowing)
- Weather- and dirt-resistant
- Scratch-, shock- and impact-resistant
- After drying resistant against water, diluted acids and bases
- Limited resistance against petrol

### Physical and chemical data

---

- **Basis of the binder:** Acrylate copolymeres
- **Colour:** transparent
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):  
glossy: 80 - 90 gloss units
- **Efficiency:**  
Depending on consistence and color of the ground:  
400 ml are sufficient for 2 m<sup>2</sup>
- **Drying time (at 20°C, 50% relative air humidity):**  
Dust-dry: after approx. 15 minutes  
Dry to touch: after approx. 30 minutes  
Cured, can be polished: after approx. 24 hours  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml

### Environment and labelling

---

**Environmentally compatible:** MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

**Labelling:** All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

---

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

**Before use, carefully read and observe the warning texts on the label!**

#### Application

- Remove rust and dirt.
- The ground has to be clean, dry and free from fat.
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of 25 cm several thin cross-coats of the clear lacquer.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

#### Tips for spray painting

---

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

#### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of January 5, 2010

This release replaces all eventually earlier issued versions.

Print date: 09.04.2020

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info@de.motipdupli.com](mailto:info@de.motipdupli.com)