

## Technical Information Rubber- & Plastic-Conditioner



Spray for the care and protection of rubber and plastic parts. Restores faded colors of rubber and plastic parts on the outside of vehicles on again. Provides a shiny appearance.

### Quality and properties

- Prevents freezing of rubber parts
- Prevents drying out of rubber parts
- Protects and preserves rubber and plastic parts
- Intensifies the color
- Protects against weather influences
- Also for removing polish residues
- pH-neutral
- Contains silicone

### Physical and chemical data

- **Smell:** Citrus
- **VOC-Content:** Approximately 93% w/w
- **Storage stability:** 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).
- **Size:** aerosol can, maximum nominal volume 600 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Bring the spray can to room temperature / Operational temperature 55 to 30°C.
- Shake before use.
- The surface should be clean and dry.
- Apply Rubber- & Plastic-Conditioner in a thin, equal layer and polish with a soft cloth.

### Order informations

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: January 10, 2014

This release replaces all eventually earlier issued versions.

Print date: 16.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)