

Technical Information Acrylic Clear Varnish



Transparent protective coating on acrylic base for thoroughly dried paintings. Applicable on wood, cardboard, stone, ceramics and many surfaces. Protects the paint coating and increases life period. Prevents the oxidation of paintable metals.

Quality and properties

- High-grade, cristal-clear acrylic protective varnish
- High gloss resp. satin matt
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Weather-resistant, light-proof, UV-resistang
- Resistant to wiping
- After drying scratch-, bump- and shock-proof
- For interior and exterior applications

Physical and chemical data

- **Basis of the binder:** Acrylate copolymeres
- **Colour:** transparent
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):
glossy: 80 - 90 gloss units
matt: 15 - 20 gloss units
- **Efficiency:**
Depending on consistence and color of the ground:
150 ml are sufficient for approx. 0.4 - 0.8 m²
400 ml are sufficient for approx. 1.0 - 2.0 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 50 minutes
Cured, can be polished: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 150 ml and 400 ml

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

- The ground has to be clean, dry and free from rust and fat.
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray in 2 minute intervals several thin cross-coats.
- Spray from a distance of approx. 25 cm
- Important: Do not spray over surfaces which are painted with synthetic resin lacquer!

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and

processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of October 27, 2011

This release replaces all eventually earlier issued versions.

Print date: 23.09.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com