

Technical Information Alkyton heat-resistant brush paint



Heat-resistant coating for application on new, bright or shot-blasted steel or well pre-treated, coated surfaces such as barbecues, heating systems, exhausts, etc. Heat-resistant up to a dry heat of 750°C.

ALKYTON heat-resistant coating is intended for small maintenance jobs and repairs.

**Products: The subpart part marker ###ITEM_LIST_EMPTY### or the template file
EXT:snet_tmpl_motip/Resources/Private/Templates/Extensions/tt_products/products_template_en.tmpl has not been found.**

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of July 5, 2010

This release replaces all eventually earlier issued versions.

Print date: 20.06.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com