

Technical Information MPL 20



MPL 20 (universal lubricant) has very good penetration properties and is indispensable for any maintenance work at home or in the workplace. It is used to remove wax, tar, oil and adhesive residues and forms a protective layer against corrosion. It loosens tight rusty screws and ensures long-lasting lubrication.

Quality and properties

- Good penetration
- Removes oil, grease, wax, Tectyl and tar from metal and rubber parts
- Cleaning effect
- Good corrosion protection
- Moisture repellent
- An invisible protective film remains after cleaning
- Directed jet spray
- This product has a special cap containing a tube and a spray head, which can be used to reach tricky places
- TRG 300 compliant

Physical and chemical data

- **Basis:** mineral oil
- **Colour:** brownish
- **Smell:** Vanilla
- **Relative density at 20°C:** 0.80 g/ml
- **Yield:** 1.98 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Temperature resistance:** -50°C to +200°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Instruction manual

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Cover coated or plastic parts with masking tape.
- Spray MPL 20 evenly on the surface to be treated.
- Optimum lubrication occurs once the solvent has evaporated.

Tips for spray painting

Protect the object and the surrounding area from spray mist. Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of: November 26, 2009

This release replaces all eventually earlier issued versions.

Print date: 20.10.2019

