

Technical Information Acryl Spray Putty



This first-class acrylic spray putty quickly and properly closes and covers little irregularities, scratches and marks from sanding at the repair spot. Results in a perfectly smooth surface for the subsequent lacquering.

The presto Acrylic Spray Putty is the ideal bonding component between the presto Polyester Putty art.no. 600054 and the following top coat.

Remark: To prime iron and steel sheet use the presto Filler.

Quality and properties

- First-class acrylic spray putty
- Can be applied in several coats
- Excellent adhesion
- Especially high filling power
- Easy to sand after a short drying time
- High coat thickness due to good stability
- Good water-resistance
- Easy to spray
- Excellent corrosion protection
- Good flow, smooth surface

Physikalische und chemische Daten

- **Basis of the binder:** Acrylic quality with special filler material
- **Colour:** grey
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): matt, 5-10 gloss units
- **Efficiency:**
Depending on consistence and color of the ground:
150 ml are sufficient for approx. 0.3 m²
400 ml are sufficient for approx. 0.8 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Can be overworked after approx. 60 minutes
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** not applicable
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 150 ml resp. 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

The most presto spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the labels!

Application

- Remove dirt, fat and oil.
- Roughen resp. grind the ground with sandpaper grain 240 up to grain 360. Rough-grinded and filled areas have to be wet-sanded. Carefully remove abrasive dust.
- Test spray at an invisible spot.
- Shake the can vigorously for approx. 3 minutes.
- Spray from a distance of approx. 25 - 30 cm.
- Apply presto Spray Putty in several thin coats. Wait after every coat for 2 - 5 minutes and shake the can before every new spray procedure.
- After approx. 1 hour, depending on weather conditions, wet-sand with sandpaper grain 400 to grain 500. The thicker the coat, the longer the drying time.
- Continue structure of paintwork with presto Filler und DUPLI-COLOR Acryl Auto-Spray.
- Coatable with synthetic and acrylic lacquers.
- Do not spray over synthetic paints!

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 29, 2010

This release replaces all eventually earlier issued versions.

Print date: 20.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com