Technical Data Sheet Linemarker



Special marking of lines and divisions for roads, parking lots and industrial plants as well as safety signs.

Colour hues: white, yellow, red, orange, green, blue, grey, black and traffic yellow.

The grey and black marking sprays can also be used as corrective sprays to remove fluorescent markings from concrete or tar.

The line marker can be used in the following accessories:

- Speedliner²
- Speedmarker long
- Speedmarker short
- Speedmarker 2-Wheel

Accessories available from all COLORMARK partners.

Quality and properties

- High coverage, quick drying quality
- Special valve for floor applications ensures sharp edges
- Specially for use in Speedliner²
- Containers: 500 ml and 750 ml
- For permanent markings (durability of the marking depends on the surface as well as location (inside /outside) and daily burden)
- Highly resistant to abrasion

Physical and chemical data

- **Colours:** white, yellow, red, orange, green, blue, grey, black, traffic yellow
- **Storage stability:**
  10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**
  Depending on condition and colour of the ground,
  500 ml are sufficient for approx. 40 m of 10 cm wide lines
  750 ml are sufficient for approx. 60 m of 10 cm wide lines
- **Drying (at 20°C, 50% relative air humidity):**
  Dust-dry: after approx. 10 minutes
  Dry to touch: after approx. 30 minutes
  Cured: after approx. 24 hours
  Can be overworked: after approx. 24 hours
  The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Contents:** aerosol cans with max. nominal volume of 500 ml resp. 750 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".
Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Shake can for approx. 3 minutes.
- After you hear the sound of the balls inside the can, vigorously shake the can for one more minute.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.
- In case of use in the Speedliner² marking trolley, attend to the corresponding manual.
- Mineral substrates must have set well, new concrete must be at least 4 - 6 weeks old
- The substrate must be dry, clean, free of fat and stable, loose and sanding layers are to remove
- Concrete and screed must still have sufficient apsorptive capacity to ensure adhesion

Tips for spray painting

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond

our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 6, 2022
This release replaces all eventually earlier issued versions.

Print date: 29.03.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com