Technical information 2K Hi-Speed Primer Filler



ColorMatic 2K hi-speed primer is universally applicable to all metallic surfaces such as steel, galvanized steel and aluminium. It offers excellent adhesion and corrosion protection and is very fast drying: 1 h (20 ° C). It is perfect for sanding, wet and dry. It is also solvent resistant.

Applications:
Ideal for spot repairs and refinishing parts.

Click here for a demonstration of the 2 K technology in a video.

Order informations

Color	Product	Bundle	Art.No.
	CM 2K Hi-Speed Grundierfü. 200	200 ml	195327
	CM 2K Hi-Speed Grundierfü. 500	500 ml	195334

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 21, 2012
This release replaces all eventually earlier issued versions.

Print date: 29.03.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com