

## Technical Information Sheet Inox Spray



Ideally suitable for sealing welding-seams and -spots at inert gas and spot welding. At spot welding between auto body sheets it protects against corrosion. ColorMatic Inox Spray is a high-quality corrosion protection but also a surface coating. Re-sprayable with all common paint systems.

**Application:** Ideal at industrial applications.

### Quality and properties

- Weldable
- Good corrosion prevention at using between auto body sheets at spot welding
- Excellent coverage
- Very good flow
- Quick-drying
- Very hard surface
- Excellent resistance to weathering
- Re-coatable with commercial coatings

### Physikalische und chemische Daten

- **Basis of the binder:** Polyvinylbutyral
- **Colour:** grey
- **Smell:** solvent
- **Efficiency:**  
Depending on consistence and color of the ground:  
400 ml are sufficient for approx. 1.0 m<sup>2</sup>
- **Drying time (at 20°C, 50% relative air humidity):**  
30-40 minutes  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 250°C
- **Storage stability:**  
Aerosols: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
Aerosoldosen, maximales Nennvolumen 400 ml
- **VOC-value:** < 268,0 g/l

### Environment and labelling

**Environmentally compatible:** MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

**Labelling:** All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Application

- Bring the can to room temperature
- The area must be dry and free of dust and grease
- Sand if necessary
- Shake can vigorously for 2 minutes
- Carry out spray test
- 2-3 coats with intermediate drying of approx. 3-5 minutes
- Don't use polyester products afterwards
- For professional use only
- Wear an appropriate respirator (recommended type A2/P3)



2 min



20 cm



20°C=  
30-40 min



approx. 1 m<sup>2</sup>



### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the

liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of May 10, 2016

This release replaces all eventually earlier issued versions.

Print date: 20.01.2021

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info@de.motipdupli.com](mailto:info@de.motipdupli.com)