Technical Information Masking Tape 60°C

Masking tape with painting quality that is highly suitable for cars, do-it-yourself and industrial use.



Quality and properties

- Suitable for masking all types of objects
- Good adhesion to metal, glass, plastics and rubber
- Does not leave any adhesive residues when used up to 60°C
- Solvent resistant
- Not UV-resistant (when used outside, remove within 8 hours of application)

Physical and chemical data

- **Adhesive:** solvent rubber
- **Carrier:** crepe paper
- **Maximum temperature:** 60°C (temporary till 80°C)
- **Tensile strength:** 85 N/ 25 mm
- **Adhesive strength:** 4 N/ 25 mm
- **Thickness:** 0,13 mm

Using instructions

Temperature: Between 0°C and +30°C.
Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 14, 2014
This release replaces all eventually earlier issued versions.

Print date: 29.03.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com