

## Technical Information Masking Tape 100°C

---

High quality masking tape in automotive standard for masking all types of objects. Maximum temperature 100°C.



### Quality and properties

---

- Good adhesion to metal, glass, plastics and rubber
- Does not leave any adhesive residues at temperatures up to 100°C
- Solvent resistant
- Not UV-resistant (when used outside, remove within 8 hours of application)

### Physical and chemical data

---

- **Adhesive:** solvent rubber
- **Carrier:** crepe paper
- **Maximum temperature:** 100°C (temporary till 110°C)
- **Tensile strength:** 85 N/ 25 mm
- **Adhesive strength:** 5 N/ 25 mm
- **Thickness:** 0,14 mm

### Using instructions

---

Temperature: Between 0°C and +30°C.

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 14, 2014

This release replaces all eventually earlier issued versions.

Print date: 14.10.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info@de.motipdupli.com](mailto:info@de.motipdupli.com)