

## Technical Information automotive HSA tape

---



Double sided foam tape with high adhesive strength. Suitable for mounting all kinds of objects such as trims, signs etc.

### Quality and properties

---

- Very high adhesive strength (HSA= high strength acrylic)
- Good adhesion to metal, glass and most plastics
- Solvent resistant
- Repositionable
- Replaces screws and pop rivets

### Physical and chemical data

---

- **Adhesive:** acrylic
- **Carrier:** acrylic foam
- **Maximum temperature:** 120°C
- **Adhesive strength:** 54 N/ 25 mm
- **Shear strength:** 7,9 kg/ cm<sup>2</sup>
- **Thickness:** 1,10 mm

### Using instructions

---

Temperature: Between 0°C and +30°C.

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

### Order information

---

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of June 26, 2014

This release replaces all eventually earlier issued versions.

Print date: 19.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)