

## Technical Information SPRAYPLAST Cleaner

---



Special Cleaner for

- Objects which you want to paint with SPRAYPLAST
- Objects which you already have painted with SPRAYPLAST

Before painting with SPRAYPLAST, remainders of fat, oil or silicone can be treated with a customary cleanser (e.g. presto Wheel Cleaner 382328). Afterwards you can clean the surface with the SPRAYPLAST Cleaner. This will optimize the adherence of the SPRAYPLAST lacquer. Even suitable to clean a surface which you already painted with SPRAYPLAST.

### Quality and properties

---

- Highly dissolving properties
- Very effective
- Pleasant scent
- Waterbased

### Physical and chemical data

---

- **Basis:** tenside solution
- **Colour:** transparent foam
- **Smell:** characteristic
- **Appearance:** foam
- **Coverage:** approx. 4 m<sup>2</sup>
- **Relative density at 20°C:** 0.96 g/ml
- **Vapour pressure at 20°C:** 3 - 4 bar
- **pH-value:** 9,5 -10,5
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 400 ml

### Environment and labelling

---

**Environmentally compatible:** MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

**Labelling:** All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

---

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Bring can to room temperature.
- Operating temperature 5° to 30° C.
- Shake for 2 minutes before use.
- Apply SPRAYPLAST Cleaner and allow to have effect.
- Remove dirt with a dry, clean cloth.

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 18, 2015  
This release replaces all eventually earlier issued versions.

Print date: 26.01.2021

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info@de.motipdupli.com](mailto:info@de.motipdupli.com)