

Technical Information Zinc Spray



Tough and long-lasting spray enriched with zinc particles for excellent corrosion protection for all iron metals such as bodywork, doors, machine, metal containers, fittings and fences etc. Apply directly to galvanised or untreated steel. Particularly suited to protecting metal surfaces prior to welding due to its excellent conductivity.

To repair or restore colour on galvanised surfaces, use MoTip Industrial Alu Zinc Spray.

Quality and properties

- Good cathodical corrosion protection
- Good filling power
- Fast drying time
- Excellent adhesion
- Spot weldable
- Resistant to petrol, chemicals and weather conditions

Physical and chemical data

- **Basis of the binder:** Epoxy-ester
- **Colour:** grey
- **Efficiency:**
Depending on consistence and color of the ground:
500 ml are sufficient for approx. 1.5 - 2.0 m²
- **Drying time (at 20°C, 50% relative air humidity)**
Dust-dry: after approx. 10 - 15 minutes
Tack-free: after approx. 20 - 30 minutes
Cured/Overworkable: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** up to 350°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol cans, maximum nominal volume 500 ml

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Instruction manuel

Before use, carefully read and observe the warning texts on the label!

Pre-treating surface:

- The surface should be clean, dry and free of grease.
- Sand old paintwork and painted parts, first.

Painting:

- The surface should be clean, dry and free of grease.
- Bring the can to room temperature.
- Operating temperature 15 to 25°C.
- Shake can for 2 minutes before use.
- Test on an inconspicuous area.
- Keep a spraying distance of 25-30 cm.
- Apply several thin coats.
- During use, shake can from time to time.
- After use, turn can upside down and spray empty to clean valve.
- Can be primed and painted once dry, if needed.

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the label!

and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of: May 7, 2010

This release replaces all eventually earlier issued versions.

Print date: 16.01.2021

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com