

## Technical Information Super Fastwax



Achieves incredibly fast long-term protection and top gloss in one step - no power-consuming polishing. High-quality maintenance product. Ideal to restore the gloss of lacquered surfaces, both metallic and non-metallic.

### Quality and properties

- Long-term protection
- Gives a glossy result
- Protects against weather influences
- Reduces the adhesion of dirt
- Contains silicone

### Physical and chemical data

- **Smell:** Characteristic
- **Basis:** Polishes and PE Wax
- **pH-value:** 7,5
- **VOC-Content:** 20% w/w
- **Storage stability:**  
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%). Store frost-free.
- **Size:**  
plastic bottle, maximum nominal volume 500 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Shake before use.
- Do not use in the blazing sun.
- The surface should be clean and dry.
- Apply presto Super Fastwax with a moist cloth in a thin, equal layer and allow to dry.
- Polish to high gloss with a dry, soft cloth.

### Order informations

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: January 10, 2014

This release replaces all eventually earlier issued versions.

Print date: 24.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)