

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DC Kreidespray
- · Article number: 133985, 133992alt, 134005alt
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- *P251* Do not pierce or burn, even after use.
- *P260 Do not breathe spray.*
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- *P501* Dispose of contents / container in accordance with regional regulations.
- · Additional information:
- EUH208 Contains fatty acids, Fatty acids, tall-oil, compds. with oleylamine. May produce an allergic reaction.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	🌣 Flam. Gas 1A, H220 Press. Gas (Comp.), H280	
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	20-<25%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide © Carc. 2, H351	2.5-<5%
CAS: 147900-93-4 Reg.nr.: 05-2114084696-34-0000	fatty acids Aquatic Chronic 2, H411 Skin Sens. 1, H317	<1%

GB

(Contd. of page 1)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

	,	ntd. of page 2)
CAS: 85711-55-3	Fatty acids, tall-oil, compds. with oleylamine	≤ 0.5%
EINECS: 288-315-1	♦ STOT RE 2, H373	
Reg.nr.: 01-2119974148-28	Eye Dam. 1, H318 Skin Sens. 1, H317	
717 - 70 00 0		
CAS: 78-93-3	butanone	≤ 0.5%
EINECS: 201-159-0	Flam. Liq. 2, H225	
Index number: 606-002-00-3	Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457290-43	EUH066	

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

(Contd. on page 4)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

- · Ingredients with biological limit values:
- 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

GB

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 3.3 Vol % (115-10-6 dimethyl ether)
 • Upper: 26.2 Vol % (115-10-6 dimethyl ether)

· Flash point: Not applicable, as aerosol.

· Decomposition temperature: Not determined.

 $\cdot pH$ Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C (68 °F): 4000 hPa (3000.2 mm Hg) (115-10-6 dimethyl ether)

· Density and/or relative density

Density at 20 °C (68 °F):
Relative density
Vapour density
Not determined.
Not determined.

9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Ignition temperature: 240 °C (464 °F) • Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 55.7 % · VOC (EC) --- 612.6 g/l · VOC-EU% 55.69 %

· Solids content:

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

43.5 %

May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids

(Contd. on page 6)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

	(Contd. of page 5)
· Self-heating substances and mixtures · Substances and mixtures, which emit flammable	Void
gases in contact with water	Void
· Oxidising liquids	Void

gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

78-93-3 butanone

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	34 mg/m3 (rat)
G1.	. /	

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 butanone List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
---------------------	--

115-10-6 dimethyl ether

EC50 / 96 h | 155 mg/l (algae)

LC50/48 h >4000 mg/l (daphnia magna)

LC50/96 h > 4000 mg/l (fish)

78-93-3 butanone

LC50 / 48 h | 308 mg/l (daphnia magna)

LC50 / 72 h 1972 mg/l (Pseudokirchneriella Subcapitata)

LC50/96 h 2990 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- $\cdot \textbf{12.3 Bioaccumulative potential} \ \textit{No further relevant information available}.$
- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$

(Contd. on page 7)

Version number 6 (replaces version 5) Printing date 24.01.2022 Revision: 24.01.2022

Trade name: DC Kreidespray

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UN1950

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport informati	on
· 14.1 UN number or ID number · ADR, IMDG, IATA	

· 14.2 UN proper shipping name

1950 AEROSOLS $\cdot ADR$ · IMDG **AEROSOLS**

 \cdot IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases. · Label 2.1

· IMDG, IATA



· Class 2.1 Gases. · Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards: Not applicable.

Warning: Gases. · 14.6 Special precautions for user

· Hazard identification number (Kemler code):

F-D,S-U· EMS Number:

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1

(Contd. on page 8)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

	(Contd. of page
	litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Category
Segregation Code	C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
<i>IMDG</i>	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
- · · ·	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

(Contd. on page 9)

Printing date 24.01.2022 Version number 6 (replaces version 5) Revision: 24.01.2022

Trade name: DC Kreidespray

(Contd. of page 8)

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GR