

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** presto finish NC-Combi-Putty
- **Article number:** 483404, 498194, 601518, 601525, 601532, 286650alt, 318658alt
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9b Fillers, putties, plasters, modelling clay
- **Process category** PROC10 Roller application or brushing
- **Application of the substance / the mixture** Knife filler/ Surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MOTIP DUPLI GmbH  
Kurt Vogelsang Strasse 6  
D-74855 Haßmersheim  
Tel.: +49/6266/75-0  
msds@de.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
Tel.: +49 6266-75-310  
Fax +49 6266-75-362  
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2      H319 Causes serious eye irritation.

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

Trade name: presto finish NC-Combi-Putty

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07

## · Signal word Warning

## · Hazard-determining components of labelling:

*n*-butyl acetate

Hydrocarbons, C9, aromatics

propan-2-ol

## · Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents / container in accordance with regional regulations.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	<i>n</i> -butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	12.5-<20%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-21194882216-32	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 9004-70-0	cellulose nitrate ⚠ Flam. Sol. 1, H228	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336	2.5-<5%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	2.5-<5%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

**Trade name: presto finish NC-Combi-Putty**

		(Contd. of page 2)
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	2.5-<5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%
CAS: 100-64-1 EINECS: 202-874-0	cyclohexanone oxime ⚠ Flam. Sol. 1, H228 ⚠ STOT RE 2, H373 ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319 Aquatic Chronic 3, H412	<2.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:** Generally the product does not irritate the skin.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

• **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

**5.3 Advice for firefighters -**

• **Protective equipment:** Mouth respiratory protective device.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

Trade name: presto finish NC-Combi-Putty

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

#### · 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

##### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>  
\*inhalable dust \*\*respirable dust

##### 34590-94-8 (2-methoxymethylethoxy)propanol

WEL Long-term value: 308 mg/m<sup>3</sup>, 50 ppm  
Sk

##### 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

· Ingredients with biological limit values:

##### xylene

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

**Trade name: presto finish NC-Combi-Putty**

(Contd. of page 4)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products

Solvent resistant gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Pasty

**Colour:** Grey

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

Trade name: presto finish NC-Combi-Putty

(Contd. of page 5)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	116 °C (240.8 °F)
· <b>Flash point:</b>	27 °C (80.6 °F)
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	500 °C (932 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1 Vol %
<b>Upper:</b>	8 Vol %
· <b>Vapour pressure at 20 °C (68 °F):</b>	6.7-8.2 hPa (5-6.2 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.5 g/cm <sup>3</sup> (12.52 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C (68 °F):</b>	1,000 s (ISO 6 mm)
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	33.3 %
<b>Water:</b>	0.4 %
<b>VOC (EC)</b>	---
	503.0 g/l
· <b>VOC-EU%</b>	33.31 %
· <b>Solids content:</b>	76.9 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

**Trade name: presto finish NC-Combi-Putty**

(Contd. of page 6)

<b>· LD/LC50 values relevant for classification:</b>		
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10,800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m <sup>3</sup> (rat)
<b>xylene</b>		
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29,000 mg/m <sup>3</sup> (rat)
<b>Hydrocarbons, C9, aromatics</b>		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (rabbit)
<b>34590-94-8 (2-methoxymethylethoxy)propanol</b>		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rab) (OECD 402)
Inhalative	LC50 / 4 h	>275 mg/m <sup>3</sup> (rat) (OECD 403)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h
<b>100-64-1 cyclohexanone oxime</b>		
Oral	LD50	883 mg/kg (rat) (OECD 401) Wert gilt für weiblich. Wert für männlich 176g mg/kg

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

<b>· Aquatic toxicity:</b>	
<b>xylene</b>	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)
<b>Hydrocarbons, C9, aromatics</b>	
EC50 / 48 h	3.2 mg/l (Daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella Subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

**Trade name: presto finish NC-Combi-Putty**

(Contd. of page 7)

**67-63-0 propan-2-ol**

LC50/96h 9,640 mg/l (pimephales promelas; 96h)

LC50 / 24 h 9,714 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**


- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**
  - **ADR, IMDG, IATA** UN1866
  - **14.2 UN proper shipping name**
  - **ADR** 1866 RESIN SOLUTION
  - **IMDG, IATA** RESIN SOLUTION
  - **14.3 Transport hazard class(es)**
  - **ADR**
- 

- **Class** 3 (F1) Flammable liquids.
  - **Label** 3

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

Trade name: presto finish NC-Combi-Putty

(Contd. of page 8)

· **IMDG, IATA**

· **Class** 3 Flammable liquids.  
· **Label** 3

· **14.4 Packing group**  
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Flammable liquids.  
· **Danger code (Kemler):** 30  
· **EMS Number:** F-E, S-E  
· **Stowage Category** A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
· **Transport category** 3  
· **Tunnel restriction code** D/E

· **IMDG**  
· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1866 RESIN SOLUTION, 3, III

\* **SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**  
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t  
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t  
· **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction:** 3

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.05.2019

Version number 7

Revision: 28.05.2019

**Trade name: presto finish NC-Combi-Putty**

(Contd. of page 9)

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Flam. Sol. 1: Flammable solids – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

GB