

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PRESTO Thermolack schwarz 250ml
- **Article number:** 287664
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use SU21** Consumer uses: Private households / general public / consumers
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTIP DUPLI GmbH
Kurt Vogelsang Strasse 6
D-74855 Haßmersheim
Tel.: +49/6266/75-0
msds@de.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS05 GHS07

· **Signal word** *Danger*· **Hazard-determining components of labelling:***butan-1-ol**Hydrocarbons, C6-C7, Isoalkane, Cyclene, <5% n-Hexane*· **Hazard statements***H225 Highly flammable liquid and vapour.**H315 Causes skin irritation.**H318 Causes serious eye damage.**H336 May cause drowsiness or dizziness.**H412 Harmful to aquatic life with long lasting effects.*· **Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P260 Do not breathe vapours.**P280 Wear eye protection / face protection.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P310 Immediately call a POISON CENTER/doctor.**P405 Store locked up.**P501 Dispose of contents / container in accordance with regional regulations.*· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

	<i>xylene, mixture of isomers</i>	<i>20-<25%</i>
	<i>Flam. Liq. 3, H226</i> <i>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315</i>	
<i>CAS: 12001-26-2</i> <i>EC number: 601-648-2</i>	<i>Mica</i> <i>substance with a Community workplace exposure limit</i>	<i>12.5-<20%</i>
<i>CAS: 100-41-4</i> <i>EINECS: 202-849-4</i> <i>Index number: 601-023-00-4</i> <i>Reg.nr.: 01-2119489370-35</i>	<i>ethylbenzene</i> <i>Flam. Liq. 2, H225</i> <i>STOT RE 2, H373; Asp. Tox. 1, H304</i> <i>Acute Tox. 4, H332</i> <i>Aquatic Chronic 3, H412</i>	<i>5-<10%</i>

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: PRESTO Thermolack schwarz 250ml

(Contd. of page 2)

EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, Isoalkane, Cyclene, <5% n-Hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-<5.0%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Kohlenwasserstoffe, C6, Isoalkane, < 5% n-Hexan Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<5.0%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<5.0%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<5.0%
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32-0032	Carbon black substance with a Community workplace exposure limit	<2.5%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1	cyclohexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	≤0.5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: PRESTO Thermolack schwarz 250ml

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Larger fires with water spray or foam. Cool containers with water
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
- **6.3 Methods and material for containment and cleaning up:**
Do not flush with water or aqueous cleansing agents
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Do not seal receptacle gas tight.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 4)

· 8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**

xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
12001-26-2 Mica	
WEL	Long-term value: 10* 0.8** mg/m ³ *total inhalable **respirable
100-41-4 ethylbenzene	
WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
71-36-3 butan-1-ol	
WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
1333-86-4 Carbon black	
WEL	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³
110-82-7 cyclohexane	
WEL	Short-term value: 1050 mg/m ³ , 300 ppm Long-term value: 350 mg/m ³ , 100 ppm

· Ingredients with biological limit values:

xylene, mixture of isomers	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· Respiratory protection:

- Not necessary if room is well-ventilated.
- Otherwise, filter class A / P2 or self contained.
- Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:

- In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 5)

- **Material of gloves** Butyl rubber, BR
- **Penetration time of glove material**
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:
Acetone: 480 min
Butyl acetate: 60 min
Ethyl acetate: 170 min
Xylene: 42 min
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	Black
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	120 °C

· **Flash point:** -1 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 430 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.1 Vol %
· Upper:	7.0 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa

· **Density at 20 °C:** 1 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic at 20 °C:	15 s (DIN 53211/4)

· **Solvent content:**

· VOC-(EU)	---
	546.1 g/l
· VOC-EU%	54.61 %

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 6)

- **Solids content:** 63.6 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

xylene, mixture of isomers

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

71-36-3 butan-1-ol

Oral	LD50	2292 mg/kg (rat) (OECD- Prüfrichtlinie 401))
		3430 mg/kg (rabbit) (OECD- Prüfrichtlinie 402)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

1333-86-4 Carbon black

Oral	LD50	10000 mg/kg (rat)
------	------	-------------------

110-82-7 cyclohexane

Oral	LD50	12705 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

xylene, mixture of isomers

LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)
EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Ecotoxicological effects:

· **Remark:** Harmful to fish

· **Additional ecological information:**

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

· Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

· **ADR** UN1263 PAINT

· **IMDG, IATA** PAINT

· 14.3 Transport hazard class(es)

· ADR



· Class

3 (F1) Flammable liquids.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: **PRESTO Thermolack schwarz 250ml**

(Contd. of page 8)

· **Label** 3· **IMDG, IATA**· **Class** 3 Flammable liquids.· **Label** 3· **14.4 Packing group**· **ADR, IMDG, IATA** II· **14.5 Environmental hazards:** Not applicable.· **14.6 Special precautions for user** Warning: Flammable liquids.· **Danger code (Kemler):** 33· **EMS Number:** F-E,S-E· **Stowage Category** B· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category** 2· **Tunnel restriction code** D/E· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 2

Revision: 17.03.2017

Trade name: PRESTO Thermolack schwarz 250ml

(Contd. of page 9)

*H318 Causes serious eye damage.**H332 Harmful if inhaled.**H335 May cause respiratory irritation.**H336 May cause drowsiness or dizziness.**H373 May cause damage to organs through prolonged or repeated exposure.**H400 Very toxic to aquatic life.**H410 Very toxic to aquatic life with long lasting effects.**H411 Toxic to aquatic life with long lasting effects.**H412 Harmful to aquatic life with long lasting effects.***Abbreviations and acronyms:***RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**ICAO: International Civil Aviation Organisation**ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*