## Technical Information Masking Tape 100°C



High quality masking tape in automotive standard for masking all types of objects. Maximum temperature 100°C.

### Quality and properties

- Good adhesion to metal, glass, plastics and rubber
- Does not leave any adhesive residues at temperatures up to 100°C
- Solvent resistant
- Not UV-resistant (when used outside, remove within 8 hours of application)

### Physical and chemical data

- **Adhesive:** solvent rubber
- **Carrier:** crepe paper
- **Maximum temperature:** 100°C (temporary till 110°C)
- **Tensile strength:** 85 N/ 25 mm
- **Adhesive strength:** 5 N/ 25 mm
- **Thickness:** 0,14 mm

### Dati per l'ordinazione

### Esonero di responsabilità

Queste informazioni tecniche si basano su conoscenze scientifiche. Sono da considerarsi tuttavia come indicazione non vincolante e non liberano il consumatore dall'effettuare personalmente i controlli sui prodotti circa la compatibilità con gli impieghi da lui previsti. L'applicazione e la lavorazione avvengono al di fuori del diretto controllo del produttore e sono di esclusiva responsabilità dell'utilizzatore. European Aerosols è sollevata da ogni responsabilità se l'eventuale danno non è riconducibile a cause specifiche imputabili alla stessa European Aerosols.

Stand: 14. August 2014
Mit dieser Version werden alle evtl. früher erschienenen Versionen ungültig.

data di stampa: 29.03.2024

European Aerosols ITALIA S.r.l | Piazza Tirana, 24/4 | 20147 MILANO | Tel 022333981 Fax 0223339611 info@it.motipdupli.com