

## Technical Information Spraygun Cleaner for sb and wb paints



ColorMatic spray gun cleaner efficiently, quickly and gently cleans spray guns of all dirt from solvent- and water-based paints. Because it is easy to use, ColorMatic spray gun cleaner saves a great deal of time and represents a portable, cost-effective alternative to a spray gun cleaning machine. It contains specific solvents, acetone and additives.

### Quality and properties

- Cleans spray gun gently, thoroughly, quickly from all impurities from solvent-based paints
- Extremely time saving
- Cost-effective alternative to spray gun cleaning machine
- Contains specific solvents, acetone and additives

### Physical and chemical data

- **Basis of binder:** solvent
- **Colour:** transparent
- **Smell:** solvent
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 267g

### Environment and labelling

**Environmentally sound:** MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling:** All products made by MOTIP DUPLI comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

- Give can a quick shake
- Carry out spray test
- Disassemble spray gun immediately after painting and thoroughly spray to wash away all paint residues
- Wipe with a clean, dry non-woven / paper towel
- Leave cleaned parts to dry thoroughly



1-2

### Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of July 26, 2010  
This release replaces all eventually earlier issued versions

Print date: 08.04.2020

MOTIP DUPLI | Wolframweg 2 | 8471 XC Wolvega | NL | [info@nl.motipdupli.com](mailto:info@nl.motipdupli.com)