

## Technical Information Magic Lights



For trendy coloured light bulbs.

Attention:

The use on motor vehicles in the area of lightening and windows is in many countries not allowed!

### Quality and properties

- High-grade nitro-combi quality
- Transparent; the structure of the ground remains visible after painting
- Durable gloss
- Excellent adhesion
- Quick drying
- Good flow, smooth surface
- Weather-resistant
- Very good colour retention (light-proof, non-yellowing)
- Scratch-, shock- and impact-resistant
- High surface hardness, good elasticity
- Attracts less dirt due to smooth surface

### Physical and chemical data

- **Basis of the binder:** Nitro-combi
- **Colour:** diverse
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): glossy, 80-85 gloss units
- **Efficiency:** not measurable
- **Drying time (at 20°C, 50% relative air humidity):**
  - Dust-dry: after approx. 10 minutes
  - Non-sticky: after approx. 15 minutes
  - Dry to touch: after approx. approx. 50 minutes
  - The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:** 5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** Touch-up pencils, nominal volume 12 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

**Before use, carefully read and observe the warning texts on the label!**

#### Application

- Thoroughly clean the object you want to paint.
- The surface has to be clean, dry and fat-free.
- Before use, shake the touch-up pencil vigorously.
- Apply just one thin coat of the lacquer.
- Use the lamp earliest after 24 hours drying time.
- Attention: the use on motor vehicles is not admitted in Germany and in many other countries. Observe the local traffic regulations!
- Before lacquering lightening bulbs you should make a test, as the adhesion cannot be granted up to every temperature level.
- Do not use on halogen bulbs!

### Order information

#### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: Dezember 1, 2009

This release replaces all eventually earlier issued versions.

Print date: 23.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)