DISTEIN

Technical Information Forestry Marking Spray Long-term



Distein Forestry Marking Spray is to be used for marking of trees, wood and stone also.
Distein Forestry Marking Spray with it's reliable adhesion on wet surfaces is weather- and water-proof.

Quality and properties

- Awarded with the „KWF-Test" approval mark
- Weather-proof, good adhesion on wet surfaces and direct insolation
- Ideal opacity and fluorescence
- Frost-proof till -20° C
- Minimal drizzle
- The special nozzle is perfect for flat spraying and wood marking
- High fertility
- Environment-neutral propellant, without CFC
- Without Toluene
- Without cadmium, lead and other heavy metal
- Easy colour-recognition with patented coloured donut
- Application is possible with metal spray handle

Physical and chemical data

- **Colours:**
  Long-term-red, Long-term-orange, Long-term-yellow, Long-term-blue, Long-term-green, long-term-white
- **Efficiency:**
  Depending on surface and colour 500 ml are sufficient for approx. 3-4 m²
- **Drying:**
  Dust-dry: after 10 minutes
  Dry to touch: after 30 minutes
  Fully dried: after 24 hours
- **Disposal:**
  Only the completely empty can should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".
- **Storage stability:**
  10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Container:**
  Maximum nominal volume = 500 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Before use, shake can well for 2 minutes.
- Spray to test colour and compatibility on an inconspicious area.
- Distance approx 10-15 cm

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of May 18, 2011
This release replaces all eventually earlier issued versions.

Print date: 28.03.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com